
fhirpath-guillotina Documentation

Release 0.4.0

Md Nazrul Islam

May 16, 2020

CONTENTS:

1	Introduction	1
1.1	Quickstart	1
1.2	Credits	3
2	Installation	5
2.1	Stable release	5
2.2	From sources	5
3	Usage	7
4	fhirpath_guillotina	9
4.1	fhirpath_guillotina package	9
5	Contributing	13
5.1	Types of Contributions	13
5.2	Get Started!	14
5.3	Pull Request Guidelines	15
5.4	Tips	15
5.5	Deploying	15
6	Credits	17
6.1	Development Lead	17
6.2	Contributors	17
7	History	19
7.1	0.4.0 (2020-05-16)	19
7.2	0.3.0 (2019-11-13)	19
7.3	0.2.0 (2019-10-10)	19
7.4	0.1.0 (2019-08-24)	19
8	Indices and tables	21
	Python Module Index	23
	Index	25

INTRODUCTION

A guillotina framework powered fhirpath provider. Full battery included to use `fhirpath` more efficiently.

If you don't know about FHIR® and HL7®, Please [have a look here](#).

1.1 Quickstart

1. Make sure `fhirpath_guillotina` is added as addon in your guillotina configure file.
2. Make sure elasticsearch server configured properly.
3. Make sure you have FHIR resource contenttypes registered (see example bellow).
4. Make sure you have FHIR resources mapping (correct version) for elasticsearch.

Example: Add Contents:

```
>>> from fhirpath_guillotina.field import FhirField

class IOrganization(IFhirContent, IContentIndex):
    index_field(
        "organization_resource",
        type="object",
        field_mapping=fhir_resource_mapping("Organization"),
        fhirpath_enabled=True,
        resource_type="Organization",
        fhir_release=FHIR_VERSION.R4,
    )
    index_field("org_type", type="keyword")
    org_type = TextLine(title="Organization Type", required=False)
    organization_resource = FhirField(
        title="Organization Resource", resource_type="Organization", fhir_release="R4"
    )

@configure.contenttype(type_name="Organization", schema=IOrganization)
class Organization(Folder):
    """
    """
```

(continues on next page)

(continued from previous page)

```
index(schemas=[IOrganization], settings={})
resource_type = "Organization"
```

Example Search:

```
>>> from guillotina.component import query_utility
>>> from fhirpath.interfaces import ISearchContextFactory
>>> from fhirpath.interfaces import IFhirSearch
>>> search_context = query_utility(ISearchContextFactory).get(
...     resource_type="Organization"
... )
>>> search_tool = query_utility(IFhirSearch)
>>> params = (
...     ("active", "true"),
...     ("_lastUpdated", "2010-05-28T05:35:56+00:00"),
...     ("_profile", "http://hl7.org/fhir/Organization"),
...     ("identifier", "urn:oid:2.16.528.1|91654"),
...     ("type", "http://hl7.org/fhir/organization-type|prov"),
...     ("address-postalcode", "9100 AA")
... )
>>> fhir_bundle = await search_tool(params, context=search_context)
>>> fhir_bundle.total == len(fhir_bundle.entry)
```

Example FhirPath Query:

```
>>> from fhirpath.interfaces import IElasticsearchEngineFactory
>>> from guillotina.component import query_utility
>>> from fhirpath.enums import SortOrderType
>>> from fhirpath.fql import Q_
>>> from fhirpath.fql import T_
>>> from fhirpath.fql import V_
>>> from fhirpath.fql import sort_
>>> engine = query_utility(IElasticsearchEngineFactory).get()
>>> query_builder = Q_(resource="Organization", engine=engine)
>>> query_builder = (
...     query_builder.where(T_("Organization.active") == V_("true"))
...     .where(T_("Organization.meta.lastUpdated", "2010-05-28T05:35:56+00:00"))
...     .sort(sort_("Organization.meta.lastUpdated", SortOrderType.DESC))
...     .limit(20)
... )
>>> query_result = query_builder(async_result=True)
>>> result = query_result.fetchall()
>>> result.header.total == 100
True
>>> len(result.body) == 20
True
>>> async for resource in query_result:
...     assert resource.resource_type == "Organization"
```

- Free software: GNU General Public License v3
- Documentation: <https://fhirpath-guillotina.readthedocs.io>.

1.2 Credits

This package skeleton was created with [Cookiecutter](#) and the [audreyr/cookiecutter-pypackage](#) project template.

CHAPTER
TWO

INSTALLATION

2.1 Stable release

To install fhirpath-guillotina, run this command in your terminal:

```
$ pip install fhirpath_guillotina
```

This is the preferred method to install fhirpath-guillotina, as it will always install the most recent stable release.

If you don't have `pip` installed, this [Python installation guide](#) can guide you through the process.

2.2 From sources

The sources for fhirpath-guillotina can be downloaded from the [Github repo](#).

You can either clone the public repository:

```
$ git clone git://github.com/nazrulworld/fhirpath_guillotina
```

Or download the [tarball](#):

```
$ curl -OL https://github.com/nazrulworld/fhirpath_guillotina/tarball/master
```

Once you have a copy of the source, you can install it with:

```
$ python setup.py install
```

CHAPTER
THREE

USAGE

To use fhirpath-guillotina in a project:

```
import fhirpath_guillotina
```


FHIRPATH_GUILLOTINA

4.1 fhirpath_guillotina package

4.1.1 Submodules

4.1.2 fhirpath_guillotina.engine module

```
class fhirpath_guillotina.engine.ElasticsearchConnection(conn)
Bases: fhirpath.connectors.factory.es.ElasticsearchConnection
Elasticsearch Connection

async count(index, compiled_query)

async fetch(index, compiled_query)
    xxx: must have use scroll+slice      https://stackoverflow.com/questions/43211387/
        what-does-elasticsearch-automatic-slicing-do      https://stackoverflow.com/questions/50376713/
        elasticsearch-scroll-api-with-multi-threading

classmethod from_url(url: str)
async scroll(scroll_id, scroll='30s')
async server_info()

class fhirpath_guillotina.engine.ElasticsearchEngine(fhir_release, conn_factory, dialect_factory)
Bases: fhirpath.engine.es.ElasticsearchEngine
Elasticsearch Engine

build_security_query(query)
calculate_field_index_name(resource_type=None, index_config=None)
    1.) xxx: should be cached

async execute(query, unrestricted=False, query_type=<EngineQueryType.DML: 'DML'>)
extract_hits(selects, hits, container)

static field_index_config_from_factory(factory, resource_type=None)
async get_index_name(container=None)
get_mapping(resource_type=None, index_config=None)
async process_raw_result(rawresult, selects)
wrapped_with_bundle(result)
```

4.1.3 fhirpath_guillotina.field module

```
class fhirpath_guillotina.field.DefaultFhirFieldSchemaSerializer(field, schema,
                                                               request)
Bases: guillotina.json.serialize_schema_field.DefaultSchemaFieldSerializer

property field_type

class fhirpath_guillotina.field.FhirField(resource_class=None,
                                            re-
                                            source_interface=None, resource_type=None,
                                            fhir_release=None, **kw)
Bases: guillotina.schema._field.Object

FhirResource also known as FHIR field is the schema field derived from z3c.form's field.

It takes all initial arguments those are derived from standard schema field, with additionally model,
resource_type and resource_interface



---



Note: field name must be start with lowercase name of FHIR Resource.



---



```
ensure_fhir_abstract(klass)

from_dict(dict_value)

from_unicode(str_val)

class fhirpath_guillotina.field.FhirFieldValue(obj: NewType.<locals>.new_type =
 None)
Bases: object

FhirFieldValue is a proxy class for holding any object derived from fhir.resources.resource.Resource

foreground_origin()
 Return the original object of FHIR model that is proxied!

patch(patch_data)

stringify(PRETTY=False)

fhirpath_guillotina.field.fhir_field_deserializer(fhirfield, value, context=None)

fhirpath_guillotina.field.fhir_field_from_resource_type(resource_type: str, cache:
 bool = True) → Optional[dict]

fhirpath_guillotina.field.fhir_field_from_schema(schema: <InterfaceClass
 zope.interface.Interface>, re-
 source_type: str = None) → Optional[fhirpath_guillotina.field.FhirField]

fhirpath_guillotina.field.fhir_field_value_serializer(value)
```


```

4.1.4 fhirpath_guillotina.helpers module

```
fhirpath_guillotina.helpers.parse_json_str(str_val: str) → Optional[dict]
```

4.1.5 fhirpath_guillotina.interfaces module

Module where all interfaces, events and exceptions live.

4.1.6 fhirpath_guillotina.utilities module

```
class fhirpath_guillotina.utilities.ElasticsearchEngineFactory
    Bases: object
        get (fhir_release=None)

class fhirpath_guillotina.utilities.FhirSearch
    Bases: object
        create_context (resource_type, fhir_release=None, unrestricted=False)

class fhirpath_guillotina.utilities.SearchContextFactory
    Bases: object
        get (resource_type, fhir_release=None, unrestricted=False)

fhirpath_guillotina.utilities.create_engine (fhir_release=None)
fhirpath_guillotina.utilities.default_settings ()
```

4.1.7 Module contents

```
fhirpath_guillotina.includeme (root)
```


CONTRIBUTING

Contributions are welcome, and they are greatly appreciated! Every little bit helps, and credit will always be given.

You can contribute in many ways:

5.1 Types of Contributions

5.1.1 Report Bugs

Report bugs at https://github.com/nazrulworld/fhirpath_guillotina/issues.

If you are reporting a bug, please include:

- Your operating system name and version.
- Any details about your local setup that might be helpful in troubleshooting.
- Detailed steps to reproduce the bug.

5.1.2 Fix Bugs

Look through the GitHub issues for bugs. Anything tagged with “bug” and “help wanted” is open to whoever wants to implement it.

5.1.3 Implement Features

Look through the GitHub issues for features. Anything tagged with “enhancement” and “help wanted” is open to whoever wants to implement it.

5.1.4 Write Documentation

fhirpath-guillotina could always use more documentation, whether as part of the official fhirpath-guillotina docs, in docstrings, or even on the web in blog posts, articles, and such.

5.1.5 Submit Feedback

The best way to send feedback is to file an issue at https://github.com/nazrulworld/fhirpath_guillotina/issues.

If you are proposing a feature:

- Explain in detail how it would work.
- Keep the scope as narrow as possible, to make it easier to implement.
- Remember that this is a volunteer-driven project, and that contributions are welcome :)

5.2 Get Started!

Ready to contribute? Here's how to set up *fhirpath_guillotina* for local development.

1. Fork the *fhirpath_guillotina* repo on GitHub.
2. Clone your fork locally:

```
$ git clone git@github.com:your_name_here/fhirpath_guillotina.git
```

3. Install your local copy into a virtualenv. Assuming you have pipenv installed, this is how you set up your fork for local development:

```
$ cd fhirpath_guillotina/
$ pipenv install --dev -e .[test]
$ pipenv shell
$ pytest tests
```

4. Create a branch for local development:

```
$ git checkout -b name-of-your-bugfix-or-feature
```

Now you can make your changes locally.

5. When you're done making changes, check that your changes pass flake8 and the tests, including testing other Python versions with tox:

```
$ make lint
$ pytest tests
$ tox
```

To get flake8 and tox, just pip install them into your virtualenv.

6. Commit your changes and push your branch to GitHub:

```
$ git add .
$ git commit -m "Your detailed description of your changes."
$ git push origin name-of-your-bugfix-or-feature
```

7. Submit a pull request through the GitHub website.

5.3 Pull Request Guidelines

Before you submit a pull request, check that it meets these guidelines:

1. The pull request should include tests.
2. If the pull request adds functionality, the docs should be updated. Put your new functionality into a function with a docstring, and add the feature to the list in README.rst.
3. The pull request should work for Python 3.7, 3.8, and optionally for PyPy. Check https://travis-ci.org/nazrulworld/fhirpath_guillotina/pull_requests and make sure that the tests pass for all supported Python versions.

5.4 Tips

To run a subset of tests:

```
$ pytest tests.test_fhirpath_guillotina
```

5.5 Deploying

A reminder for the maintainers on how to deploy. Make sure all your changes are committed (including an entry in HISTORY.rst). Then run:

```
$ bumpversion patch # possible: major / minor / patch  
$ git push  
$ git push --tags
```

Travis will then deploy to PyPI if tests pass.

**CHAPTER
SIX**

CREDITS

6.1 Development Lead

- Md Nazrul Islam <email2nazrul@gmail.com>

6.2 Contributors

None yet. Why not be the first?

HISTORY

7.1 0.4.0 (2020-05-16)

Improvements

- supports `fhirpath` 0.6.1 or later version.
- supports `guillotina` 5.3.x but not 6.x.x

7.2 0.3.0 (2019-11-13)

Improvements

- supports <https://pypi.org/project/fhirpath/> 0.4.0 or later version.

7.3 0.2.0 (2019-10-10)

- Full (almost) featured [FHIR](#) Search R4 supports.

7.4 0.1.0 (2019-08-24)

- First release on PyPI. [nazrulworld]

**CHAPTER
EIGHT**

INDICES AND TABLES

- genindex
- modindex
- search

PYTHON MODULE INDEX

f

`fhirpath_guillotina`, 11
`fhirpath_guillotina.engine`, 9
`fhirpath_guillotina.field`, 10
`fhirpath_guillotina.helpers`, 11
`fhirpath_guillotina.interfaces`, 11
`fhirpath_guillotina.utilities`, 11

INDEX

B

build_security_query()
(*fhirpath_guillotina.engine.ElasticsearchEngine*
method), 9

C

calculate_field_index_name()
(*fhirpath_guillotina.engine.ElasticsearchEngine*
method), 9

count() (*fhirpath_guillotina.engine.ElasticsearchConnection*
method), 9

create_context() (*fhirpath_guillotina.utilities.FhirSearch*
method), 11

create_engine() (in
fhirpath_guillotina.utilities), 11

D

default_settings() (in
fhirpath_guillotina.utilities), 11

DefaultFhirFieldSchemaSerializer (class in
fhirpath_guillotina.field), 10

E

ElasticsearchConnection (class
fhirpath_guillotina.engine), 9

ElasticsearchEngine (class
fhirpath_guillotina.engine), 9

ElasticsearchEngineFactory (class
fhirpath_guillotina.utilities), 11

ensure_fhir_abstract()
(*fhirpath_guillotina.field.FhirField* method),
10

execute() (*fhirpath_guillotina.engine.ElasticsearchEngine*
method), 9

extract_hits() (*fhirpath_guillotina.engine.ElasticsearchEngine*
method), 9

F

fetch() (*fhirpath_guillotina.engine.ElasticsearchConnection*
method), 9

fhir_field_deserializer() (in
fhirpath_guillotina.field), 10

fhir_field_from_resource_type() (in module
fhirpath_guillotina.field), 10

fhir_field_from_schema() (in module
fhirpath_guillotina.field), 10

fhir_field_value_serializer() (in module
fhirpath_guillotina.field), 10

FhirField (class in *fhirpath_guillotina.field*), 10

FhirFieldValue (class in *fhirpath_guillotina.field*),
10

fhirpath_guillotina
module, 11

fhirpath_guillotina.engine
module, 9

fhirpath_guillotina.field
module, 10

fhirpath_guillotina.helpers
module, 11

fhirpath_guillotina.interfaces
module, 11

fhirpath_guillotina.utilities
module, 11

FhirSearch (class in *fhirpath_guillotina.utilities*), 11

field_index_config_from_factory()
(*fhirpath_guillotina.engine.ElasticsearchEngine*
static method), 9

field_type() (*fhirpath_guillotina.field.DefaultFhirFieldSchemaSerializer*
property), 10

foreground_origin()
(*fhirpath_guillotina.field.FhirFieldValue*
method), 10

from_dict() (*fhirpath_guillotina.field.FhirField*
method), 10

from_unicode() (*fhirpath_guillotina.field.FhirField*
method), 10

from_url() (*fhirpath_guillotina.engine.ElasticsearchConnection*
method), 10

get() (*fhirpath_guillotina.utilities.ElasticsearchEngineFactory*
method), 11

get() (*fhirpath_guillotina.utilities.SearchContextFactory*
method), 11

G

```
get_index_name () (fhirpath_guillotina.engine.ElasticsearchEngine
                  method), 9
get_mapping () (fhirpath_guillotina.engine.ElasticsearchEngine
                  method), 9
```

I

```
includeme () (in module fhirpath_guillotina), 11
```

M

```
module
    fhirpath_guillotina, 11
    fhirpath_guillotina.engine, 9
    fhirpath_guillotina.field, 10
    fhirpath_guillotina.helpers, 11
    fhirpath_guillotina.interfaces, 11
    fhirpath_guillotina.utilities, 11
```

P

```
parse_json_str ()           (in module
                           fhirpath_guillotina.helpers), 11
patch ()          (fhirpath_guillotina.field.FhirFieldValue
                  method), 10
process_raw_result ()        (fhirpath_guillotina.engine.ElasticsearchEngine
                             method), 9
```

S

```
scroll () (fhirpath_guillotina.engine.ElasticsearchConnection
            method), 9
SearchContextFactory      (class in
                           fhirpath_guillotina.utilities), 11
server_info () (fhirpath_guillotina.engine.ElasticsearchConnection
                method), 9
stringify () (fhirpath_guillotina.field.FhirFieldValue
               method), 10
```

W

```
wrapped_with_bundle ()        (fhirpath_guillotina.engine.ElasticsearchEngine
                            method), 9
```